

Votre revendeur :

Design pratique et distingué

# Propos®

## 800

FIABLE, ÉLÉGANT, ÉCONOMIQUE, DESIGN INTÉLLIGENT

- Installation & maintenance facilité par le design
- Performances optimisées, Design basse consommation
- Intel® D2550 Fanless 2GB RAM (DDR3)
- LCD L.E.D 15» Pouces



## Options



### Compact Design

- Fits seamlessly into any store environment



### Magnetic Stripe Reader (MSR) Smart Card Reader (SCR)



### Durable and Stable Stand

- A functional, cable management
- Sturdy base design offers



### Customer Display

- VFD type
- 20 columns x 2 lines



### 2nd LCD Display

- 12.1", 10.4", 10.1" display
- 1024 x 768 resolution



Intel Atom  
QuadCore  
64bits



SSD



DDR3



LCD

# Propos<sup>®</sup> 800



Intel Atom  
QuadCore  
64bits



SSD



DDR3



LCD

## Specifications



|                              | PROPOS 800 Core i3/i5/i7  | PROPOS 800 D2550  |
|------------------------------|---|---|
| <b>CPU</b>                   | uPGA988 for 3rd Generation Intel® Core™ i7/i5/i3 (Ivy Bridge), 2nd Generation Intel® Core™ (Sandy Bridge) - Intel® Core™ i7 3940XM Processor (8M Cache, up to 3.90 GHz) | Intel Atom processor D2550 (1MB Cache, 1.86 GHz, Dual Core for Cedarview-D) |
| <b>Chipset</b>               | Intel QM77  | Intel NM10  |
| <b>Storage</b>               | SATA 3 (6Gb/s) 2.5 inch HDD or SSD  | SATA 2 (3Gb/s) 2.5 inch HDD or SSD  |
|                              | Support Raid 0, 1   | -   |
|                              | Support AHCI  | -   |
| <b>Memory</b>                | DDR3-1600MHz SODIMM Default 2GB (MAX. 8GB)  | DDR3-1066MHz SODIMM 2GB (MAX. 4GB)  |
| <b>Graphic</b>               | Integrated Intel GFX  | Integrated Intel GMA HD 3650  |
| <b>AMT</b>                   | Support iAMT 8.0  | -   |
| <b>Display</b>               |   |   |
| <b>Resolution</b>            | 15" LED Backlight TFT-LCD 250 cd/m <sup>2</sup> (1024 x 768 resolution)   |   |
| <b>Touch screen</b>          | 5-wired Resistive Touch   |   |
| <b>Internal I/O</b>          |   |   |
| <b>USB</b>                   | 3 Ports (reserved for touch controller, SCR EMV card, camera and MSR controller)  |   |
| <b>Serial port</b>           | COM 5 (reserved for cash drawer port) & COM 6 (reserved for MSR)  |   |
| <b>Display port</b>          | LVDS or VGA & COM 4 (reserved for CDP)  | VGA & COM 4 (reserved for CDP)  |
| <b>Extension slot</b>        | Mini PCIe   |   |
| <b>Primary display</b>       | 24bit LVDS  |   |
| <b>External I/O</b>          |   |   |
| <b>USB</b>                   | Rear 6 (USB 3.0 x 4 ports, USB 2.0 x 2 ports)   | Rear 4 (USB 2.0 x 4 ports)  |
| <b>PS/2</b>                  | 1 Port (reserved for Keyboard & Mouse)  |   |
| <b>Serial port</b>           | COM 1 ~ 3 with 5V/12V power output on 9pin  |   |
| <b>LAN</b>                   | Gigabit Ethernet x 2 ports<br>1x Intel Gigabit LAN with iAMT 8.0 (Intel 82579LM)<br>1x Intel Gigabit LAN with (Intel 82583V)  | Realtek RTL 8111E Ethernet Controller                                       |
| <b>Audio</b>                 | Realtek ALC 892 / Line-out, Mic-in  |   |
| <b>Display port</b>          | VGA x 1 port  |   |
| <b>Options</b>               |   |   |
| <b>MSR</b>                   | Comply with ISO 7811, Support 1 & 2 & 3 track   |   |
| <b>USB</b>                   | 2 Ports (USB 2.0)   |   |
| <b>Serial port</b>           | COM5 (support 9pin header or DB9, shared with cash drawer port)   |   |
| <b>SCR</b>                   | EMV level 1   |   |
| <b>Dallas</b>                | Dallas I-button reader  |   |
| <b>Customer display</b>      | VFD type (20 x 2)   |   |
| <b>2nd LCD</b>               | 10.1" LCD or 10.4" LCD or 12.1" LCD (1024 x 768 resolution)   |   |
| <b>Cash drawer port</b>      | 1 Port  |   |
| <b>Parallel port</b>         | 1 Port  |   |
| <b>WiFi</b>                  | Mini PCIe for wireless LAN  |   |
| <b>Operating Temperature</b> | 0°C ~ 40°C at 10% ~ 80% humidity  |   |
| <b>Storage Temperature</b>   | -20°C ~ 60°C at 10% ~ 80% humidity  |   |
| <b>Qualification</b>         | CE, FCC, KC   |   |
| <b>Power</b>                 | Adaptor 24V, 6A   | Adaptor 12V, 5A   |
| <b>OS Support</b>            | Windows 7, Windows 8, POS Ready 7   | Windows XP/Vista, Windows 7, POS Ready 2009/7                               |
| <b>Dimension (WxHxD)</b>     | 364 x 300 x 227(mm), 14.3 x 11.8 x 8.9(inch)  |   |